



## ROUNDED RECTANGLE MIXER & SPOUT BACKPLATE



Section View A-A



Front View

Note: Dimensions are nominal measurements only


SPECIFICATIONS	
RECOMMENDED USE	Domestic
MATERIAL	Solid Brass

## **INSTALLATION GUIDE**

Note: This product must be installed by a licensed plumber. This is a general installation guide - there are many factors that are involved that can alter the installation method. This product install must comply with AS/NZS 3500.



USE ROUGH-IN TEMPLATE PROVIDED TO ENSURE ACCURATE POSITIONING





Regularly clean with mild liquid detergent or soap and water



DO NOT use cream cleaners or bleach. These substances are abrasive




DO NOT use cleaning pads with abrasive surfaces as this may scratch the material



# WALL MOUNTED SPOUT





Note: Dimensions are nominal measurements only


SPECIFICATIONS	
RECOMMENDED USE	Domestic
MATERIAL	Solid Brass
TEMPERATURE RATING	Maximum continuous working temperature 75°C If the water temperature exceeds 75°C, an approved tempering valve must be fitted
PRESSURE RATING	Recommended minimum working pressure 150kPa Recommended maximum working pressure 500kPa Hot and cold water inlet pressure should be equal
	WELS 5 Star, 5.5L/min, T40323


Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors. All ABI Products are designed in Australia. Copyright ABI Interiors Pty Lty 2021.

## **INSTALLATION GUIDE**

Note: This product must be installed by a licensed tradesperson. This is a general installation guide - there are many factors that are involved that can alter the installation method. All work carried out must comply and be according to AS/NZS 3500.









Regularly clean with mild liquid detergent or soap and water



DO NOT use cream cleaners or bleach. These substances are abrasive




DO NOT use cleaning pads with abrasive surfaces as this may scratch the material




# MILANI PROGRESSIVE HANDLE SET

## lust Colour Parts





## In Wall



Disclaimer: To achieve infiniti (interchangeable sleeves) finish wall must fall between Point A and B. Your In-Wall component must be installed without the sleeve attached, please ensure that your chosen sleeve doesn't break your waterproofing seal.

**Note:** Dimensions are nominal measurements only

Domestic
Recommended minimum working pressure 150kPa Recommended maximum working pressure 500kPa Hot and cold water inlet pressure should be equal
Maximum continuous working temperature 75°C If the water temperature exceeds 75°C, an approved tempering valve must be fitted
Storage tank: Yes Continuous Flow: Yes Gravity Feed: Not suitable

Disclaimer: Products in this specification manual must by regulation be installed by licensed and registered trade people. The manufacturer/distributor reserves the right to vary specifications or delete models from their range without prior notification. Dimensions are nominal measurements only. Dimensions and set-outs listed are correct at time of publication however the manufacturer/distributor takes no responsibility for printing errors. All ABI Products are designed in Australia. Copyright ABI Interiors Pty Lty 2021.

### **INSTALLATION GUIDE**

Note: This product must be installed by a licensed plumber. This is a general installation guide - there are many factors that are involved that can alter the installation method. This product install must comply with AS/NZS 3500.




Fasten screws to secure the wall mixer into wall structure



Attach water supply and water outlet. TEST AND CHECK FOR LEAKS.





Create a 47mm hole in cement sheet (3) and tiles. Waterproof at this point if future sleeve change is desired. DO NOT WATERPROOF SLEEVE.


> Please ensure that the hole is big enough to allow for the sleeve to slide on at fit-off stage.




past this point for the small sleeve

past this point for the large sleeve


Push the sleeve over the body until it is as far back as possible and nut thread is exposed. Screw the dome onto the brass fitting and tighten.



Place the handle onto the fitting. (5) Fasten the grub screw firmly with the



#### HOW TO CUSTOMIZE YOUR MIXER





STEP 2: Remove the handle, dome and sleeve from your mixer & repeat steps above for installation! (Ensure waterproofing was conducted prior to sleeve install).

STEP 3: Be sure to get this checked by your plumber prior to using

#### WHAT'S IN THE BOX **EXPLODED VIEW**

- 1. Long Sleeve
- 2. Dome
- 3. Back Plate 4. Handle
- 5. Allen Key
- 6. Short Sleeve







Regularly clean with mild liquid detergent or soap and water



DO NOT use cream cleaners or bleach. These substances are abrasive



DO NOT use cleaning pads with abrasive surfaces as this may scratch the material